

PRESS RELEASE

for immediate attention

August 2012

Press contact: David Denyer

07976 646 404

david@ddpr.co.uk

Introducing Icon Audio's first stereo power amplifier: the 60P MkIIIm

The Icon Audio Stereo 60P MkIIIm is a high-powered stereo amplifier designed to get the very best performance from virtually any pre-amplifier, whether it is valve, hybrid, transistor, transformer or passive. It has no input selector and no volume control. It is a pure power amplifier in which the input socket is directly connected to the grid of the first valve.

The massive power supply, low distortion tertiary (LDT) output transformers, and the excellent KT120 valve combine to produce a ground-shaking 80 watts per channel. Ideal for users seeking a very fast and dynamic sound, the ST60P MkIIIm will deliver the power of rock music and the finest detail of modern recordings without harshness. Some audiophiles prefer the sweetness of triode operation. The Stereo 60P MkIIIm is able to change from an ultralinear 80 watt per channel amplifier to a 40 watt triode amplifier at the flick of a switch.

High output valve amplifiers work better with 'fixed' bias but this needs occasional checking. The Stereo 60P MkIIIm features a built-in bias meter which greatly simplifies keeping the amplifier in peak performance.

Every Icon Audio amplifier is finished and tested by Icon's team of engineers in Leicester, and can be ordered as a 'David Shaw Signature' version featuring Jensen copper foil oil-in-paper capacitors and premium valves.

Features: Icon Audio Stereo 60P MkIIIm

- Switchable ultralinear / triode operation modes
- Class A triode front end
- Switchable input sensitivity for use with both active and passive preamps
- Custom hand wound Low Distortion Tertiary (LDT) output transformers
- 4 x KT120 output valves (compatible with KT88 / 6550)
- 2 x 6SL7 first stage valves
- 2 x 6SN7 output driver valves
- OD3 valve voltage regulator
- Hand wired "Point to Point" for the best sound quality and reliability
- PTFE insulated silver plated pure copper wiring

- Built-in 'easy bias' meter
- Gold plated input and loudspeaker terminals
- Attractive valve cover included
- CE, ROHSS & WEEE compliant.

Technical specifications

Page | 2

Output power	80 W RMS ultralinear mode 35 W RMS triode mode
Gain	70 dB high sensitivity 20 dB low sensitivity
Frequency response	20 Hz – 55 kHz \pm 3 dB
Signal to noise ratio	-97 dB
Total harmonic distortion	0.25 % @ 40 W (1 kHz)
Power consumption	240 watts typical 500 watts maximum
Dimensions (H x W x D)	230 x 440 x 400 mm
Weight	35 kg
Warranty	1 year

UK selling price (inc. VAT)

Icon Audio Stereo 60P MkIIIm	£2,199.95
Icon Audio Stereo 60P MkIIIm David Shaw Signature edition	£2,679.95

AVAILABLE NOW

About Icon Audio

The Icon Audio philosophy is to create audiophile products that sound good, look good, are easily affordable and will last a lifetime.

Each Icon Audio amplifier is designed in Leicester, UK, by the company's founder, David Shaw. The amplifier chassis are then manufactured in China, with production and quality control being closely managed by David himself who regularly travels to China to ensure that the performance and quality on which Icon Audio have built their reputation are fully maintained. Final product assembly, custom modifications and extensive testing then take place in Icon's premises in Leicester, UK.

Everything in an Icon Audio amplifier is serviceable and replaceable, from the valves themselves to substantial components such as the transformers. All Icon Audio products are available for demonstration by appointment in Leicester and also via a selected dealer network.

Consumer contact

Icon Audio
351 Aylestone Road
Leicester
LE2 8TA

Tel: 0116 244 0593
Email: sales@iconaudio.co.uk
Website: www.iconaudio.com

Page | 3

Press contact

For more information, product samples or high-resolution print-ready images please contact David Denyer on 07976 646 404 or david@ddpr.co.uk.



Tel: 07976 646 404
Email: david@ddpr.co.uk
www.daviddenyerp.co.uk

Ends / ©DDPR / NO EMBARGO