



PRESS RELEASE
for immediate attention
March 2020

Press contact: David Denyer
07976 646 404
david@ddpr.co.uk

Clearaudio upgrades Basic & Balance phonostages to new V2 editions



Basic V2



Balance V2

A fine **Balance** of simplicity with complexity, and a multi-award winner that's anything but **Basic**: Clearaudio's ever-popular duo of mid-priced phonostages offer a raft of covetable options for the high-end audio beginner or upgrader – and both have now been treated to their own upgrade.

Balance V2

Preamplifier, phonostage and headphone amplifier - Clearaudio's new Balance V2 combines three key devices in one, so there are options here for every type of vinyl spinner. The new V2 advances the technologies of the previous Balance Plus, while retaining the latter's impressive array of options for adjusting and fine-tuning its performance to your particular system and preferences. Even so, this unit's design remains elegantly unfussy and its operation effortlessly intuitive, moving between modes at the flick of a switch.

The Balance V2 features a fully balanced circuit design with completely independent circuitry for left and right channels, giving excellent stereo separation and a realistic soundstage.

Its volume control allows the unit to be connected directly to a power amplifier or to an active loudspeaker system. As well as the usual RCA outputs, the Balance V2 features balanced XLR outputs and a 6.3mm plug headphone output. A simple switch allows you to choose between moving magnet and moving coil mode. From there, the Balance V2 will automatically harmonize with almost any high-end phono cartridge without you needing to make any further adjustments.

High precision RIAA equalization achieves an accuracy of within 0.1dB, while an optional subsonic filter attenuates any unwanted low frequency noise. A separate power supply in its own sleek, resonance-shielding aluminium casing keeps any potential interference at bay.

With this small yet high-performance package, Clearaudio effectively balances audiophile-quality technology with a simplicity that can be enjoyed by any music enthusiast.

Basic V2

There's actually nothing 'basic' about the Basic V2 phonostage. Don't be fooled by its cool, minimalist design. Within that sleek aluminium casing (with silver or black anodized finish) lies an inner world of highly refined features. Its predecessor, the Basic Plus, was a multi-award winner and with the V2, Clearaudio has taken all of that 'Plus' technology up a notch.

Page | 2

On the outside, there's just one visible control: a single power switch on the upper surface that opens up a raft of possibilities. On the underside you can switch between moving coil and moving magnet mode. Like the Balance V2, the Basic V2 is compatible with almost any high-end phono cartridge without making any further adjustments.

Or, you can choose from a range of performance enhancing settings to fine-tune its parameters to your system and your heart's content. An optional subsonic filter attenuates any unwanted low frequency noise, while RIAA equalization accuracy is again within 0.1dB.

All of which adds up to the Basic V2 being the perfect all-rounder for both audiophiles and music lovers. Tweak away, or sit back and relax knowing you're in the best possible hands - your choice entirely.

Technical specifications

	Balance V2	Basic V2
Mode	MM / MC (switchable subsonic filter)	
Gain @ 1kHz	+46dB (MM mode) +66dB (MC mode)	
Input impedance	47 kOhm / 270pF (MM mode) 500 Ohm / 270pF (MC mode)	
RIAA accuracy	± 0.1dB	
THD	< 0.001% (IEC A)	< 0.002% (IEC A)
Signal/noise ratio	-78db (MM mode) -69dB (MC mode)	-72db (MM mode) -67dB (MC mode)
Channel separation	> 92dB (@ 1kHz)	> 90dB (@ 1kHz)
Subsonic filter	20Hz (-6dB / Oct.; switchable on bottom panel)	20Hz (-18dB / Oct.; switchable on bottom panel)
Power consumption	Max. consumption: 6.6 watts Standby mode: <0.3 watts	Max. consumption: 3 watts Standby mode: <0.3 watts
Output connections	Unbalanced (RCA) Balanced (XLR) Headphone output (6.3mm jack)	Unbalanced (RCA)
Weight	Approx. 2.3kg (phonostage) Approx. 1.4kg (power supply)	Approx. 1.2kg (phonostage and power supply)
Dimensions (w x d x h) / mm	Phonostage: 240 x 158 x 62 Power supply: 240 x 145 x 62	Phonostage: 118 x 158 x 42 Power supply: 100 x 55 x 80

Pricing and availability

The Balance V2 and Basic V2 are available now, priced at £2,510 and £990 respectively (inc. VAT).

Consumer contacts for publication

Page | 3

www.clearaudio.de

UK distributor:

Sound Fowndations
Aldermaston
Berkshire

Tel: 0118 981 4238
Email: info@soundfowndations.co.uk
Web: www.soundfowndations.co.uk

Press contact

For more information, product samples or high-resolution print-ready images please contact David Denyer on 07976 646 404 or david@ddpr.co.uk.

Ends / ©DDPR / No embargo

| David Denyer PR |

Tel: 07976 646 404
Email: david@ddpr.co.uk
www.daviddenyerpr.co.uk

 DavidDenyerPR  @DaveDenyer