



PRESS RELEASE
for immediate attention
September 2022

Press contact: David Denyer
07976 646 404
david@ddpr.co.uk

Exposure completes 3510 series with new mono power amplifiers



The new 3510 series

In 2021, British hi-fi brand Exposure launched a new, updated version of its upper end series of components with the 3510 integrated amplifier, closely followed by a 3510 pre/power amplifier combination. Now, the series is completed with the brand's new 3510 mono power amplifiers.

Exposure's 3510 series shares many design elements with the brand's top-of-range 5010 series.

Key features of the new mono power amplifiers include:

- High capacity power supply circuit designed around a large custom-made toroidal transformer and massive smoothing capacitors to ensure a high current reserve for the output stage with electronic smoothing for low noise on the supply rails to the gain stage.
- All bipolar transistor design using carefully selected parts.
- DC coupled throughout.
- Balanced and unbalanced inputs, enabling compatibility with a wide variety of preamplifiers.
- Bi-wire speaker outputs using high quality shrouded sockets.
- An electronic, non-invasive overload protection circuit and thermal trip ensure that these amplifiers should last a lifetime.

These monos deliver an impressive 100W RMS per channel into 8 Ohms, making them ideal for driving difficult speaker loads. Expect enhanced linearity and lower distortion at high power output.

The 3510 series features Exposure's signature minimalist design, with full aluminium casework and extruded front panel to control resonance and stray electro-magnetic fields. Available in black or titanium, all components come with a three year guarantee.

Technical specifications

| | |
|---------------------------|--|
| Power output | 100W per channel, 8 Ohms |
| Frequency response | -3dB @ 60kHz, ref 1kHz |
| Total harmonic distortion | <0.01% @1kHz, ref rated power |
| Signal to noise ratio | >110dB, A weighted, ref rated output |
| Input impedance | 50k Ohms @ 1kHz (unbalanced input) |
| Input sensitivity | 1.75V @ 1kHz (unbalanced input) 875mV @ 1kHz (balanced input) |
| Power consumption | <400W, 8 Ohms load |
| Dimensions | 115mm (h) x 440mm (w) x 300mm (d) |
| Weight | 12kg net (unpackaged) / 14kg gross (packaged) |

Pricing & availability

The Exposure 3510 mono power amplifiers are available now, priced at £2,990 per pair (incl. VAT).

Consumer contacts for publication

For more information and to find your local retailer:

Exposure Electronics

West Sussex

Web: www.exposurehifi.com

Tel: 01273 423 877

Press contact

For more information, product samples or high-resolution print-ready images please contact David Denyer on 07976 646 404 or david@ddpr.co.uk.

Ends / ©DDPR / No embargo

| David Denyer PR |

Tel: 07976 646 404

Email: david@ddpr.co.uk

www.daviddenyerp.co.uk

 DavidDenyerPR  @DaveDenyer