



PRESS RELEASE
for immediate attention
July 2026

Press contact: David Denyer
07976 646 404
david@ddpr.co.uk

Exposure adds mono power amplifiers to new flagship 5510 series



Exposure Electronics' new 5510 Series represents the pinnacle of Exposure engineering, bringing greater scale, grip and refinement to every part of the musical performance. Designed as a true flagship family, the series' components share a calm authority that lets your music unfold with effortless clarity and control. The presentation is spacious, dynamic and beautifully composed, revealing subtle textures while delivering the drive and impact that define real high-end sound. Every element of the design works quietly in the background to reduce noise, enhance stability and preserve the natural flow of the recording.

The 5510 mono power amplifiers, Exposure's latest addition, are the pinnacle of this series. Paired with the 5510 preamplifier, they form the ultimate three-chassis amplifier system, offering a level of transparency, power and musical engagement that stands at the very top of the Exposure range. They are built for listeners who want the purest connection to their music.

Key technical features:

- **Power supply:** Equipped with a large, custom-made toroidal transformer and high-quality screw-terminal smoothing capacitors.
- **Circuitry:** All-bipolar transistor design utilising carefully selected components and fully DC-coupled topology. Built to drive difficult, low-impedance loudspeaker loads effortlessly.
- **Protection:** Includes a non-invasive overload protection circuit and a thermal trip.

- **Connectivity:** Balanced and unbalanced inputs. Bi-wire speaker outputs using high quality shrouded 4mm sockets.
- **Chassis:** High-grade, resonance-controlling all aluminum casework, available in black.
- **Warranty:** Backed by a 3-year manufacturer's guarantee.

Your music, your way.

Specifications

Power output	200 W into 8 Ω , 370 W into 4 Ω
Input impedance	75 k Ω @ 1 kHz (unbalanced input)
Frequency response	-3 dB at 52 kHz, ref. 1 kHz (unbalanced input)
Total harmonic distortion	<0.015% @ 1 kHz, 200 W into 8 Ω , <0.005% @ 1 kHz, 100 W into 8 Ω
Signal-to-noise ratio	>120 dB (A-weighted), ref. 200 W into 8 Ω , >100 dB (A-weighted), ref. 1 W into 8 Ω
Mains supply	110/120 V or 220/240 V, 50/60 Hz (factory set)
Power consumption	<800 VA, 8 Ω load
Dimensions	440mm (w) \times 115mm (h) \times 300mm (d)
Net weight	14 kg
Gross weight	16 kg

Pricing & availability

The Exposure 5510 mono power amplifier is available now, priced at £7,300 (incl. VAT) per pair.

Consumer contact for publication

Exposure Electronics Ltd	Tel: 01273 423 877
Lancing, West Sussex	Web: www.exposurehifi.com

Press contact

For more information, product samples or high-resolution print-ready images please contact David Denyer on 07976 646 404 or david@ddpr.co.uk.

Ends / ©DDPR / No embargo

| David Denyer PR |

www.daviddenyerp.co.uk

07976 646 404

david@ddpr.co.uk